

# IMPORTANT SAFETY INSTRUCTIONS

When using an electrical furnishing, basic precautions should always be followed, including the following. Read all instructions before using (this furnishing).

**DANGER** - To reduce the risk of electric shock:

Always disconnect this furnishing from the electrical outlet before cleaning.

**WARNING** -To reduce the risk of burns, fire, electric shock, or injury to persons.

1. Disconnect from outlet before putting on or taking off parts.
2. Close supervision is necessary when this furnishing is used by, or near children, invalids, or disabled persons.
3. Use this furnishing only for its intended use as described in these instructions. Do not use attachments not recommended by the manufacturer.
4. Never operate this furnishing if it has damaged, not working properly, dropped or damaged, or dropped into water. Return the furnishing to a service center for examination and repair
5. Keep the cord away from heated surfaces.
6. Never operate the furnishing with the air openings blocked. Keep the air openings free of lint, hair, and the like.
7. Never drop or insert any object into any opening.
8. Do not use outdoors.
9. Do not operate where aerosol (spray) products are being used or where oxygen is being administered.
10. To disconnect turn all controls to the off position, then disconnect from outlet.
11. For grounded products the following statement:  
"WARNING: Risk of Electric Shock - Connect this furnishing to a properly grounded outlet only. See Grounding Instructions.

## SAVE THESE INSTRUCTIONS


### 12. GROUNDING INSTRUCTIONS

This product must be connected to a grounded metal, permanent wiring system, or an equipment-grounding conductor must be run with the circuit conductors and connected to the equipment-grounding terminal or lead on the product.

# PRODUCT MANUAL

Model: KL910702  
KLRA4E08060H2B1P0D  
KLRA4E09070H2B1P0D  
KLRA4E060100H2B1P0D

## LED MIRROR



## FEATURES

- 5mm Copper free mirror.
- PVC backed.
- Mounting type: Vertically or horizontal.
- Energy Efficient and Long Lasting LED Lighting.
- 3 Pin Plug/Hardwired.

## LIGHTING:

- LED (Light-Emitting Diode).
- Defogger .
- Color Changeable.
- Power Source: Input: 110volts,50/60HZ.
- Energy saving LED lifetime approx 50,000 hours.

## AVAILABLE STANDARD SIZE:

26"X 39"






## CERTIFICATION:



Intertek  
5020102

# MANUAL INSTRUCTION

## HOW TO USED DEFOGGER SWITCH AND DIMMER SWITCH ?

- 1) Short Touch Button  (<1s) to turn the task light ON/OFF.  white is ON, blue is OFF.
- 2) Short Touch Button  (<1s) to change color temperature from 2800K to 6000K, and cycle.
- 3) Press the Button  to turn the defogger ON/OFF.  white is ON, blue is OFF.

## ELECTRICAL SAFETY INSTRUCTIONS

All connections must be installed by a licensed electrician, in accordance with current building codes. Consult a qualified electrician.

## IMPORTANT

Always switch off the electrical supply at the main during installation and maintenance. It is recommended that the circuit breaker is switched off for the necessary circuit before installation commences.

Fitting in Bathrooms is subject to the appropriate building code Regulations. This product is NOT suitable for outside zones. It is also Not suitable for installation in saunas, steam rooms or shower cubicles. This product is only suitable for permanent installation. **DO NOT** connect to a trailing plug and socket outlet. This product is only suitable for indoor use. Do not attach the product to surfaces that are damp or otherwise electrically conductive.

## INSTALLATION CARE & SAFETY

Wear suitable eye protection when drilling. Take care when using power tools. Beware of hidden cables or pipes. Take care if drilling on tiled surfaces in case the drill slips. A piece of masking tape applied to the wall before marking out the fixing holes will stop the drill from wandering.


## CLEANING

It is recommended that the unit is cleaned with a soft, dry, non abrasive cloth when turned off. Never use cleaning agents or abrasive materials on any type of surface finish. Do not allow moisture to come into contact with the electrical components.


## IMPORTANT

DO NOT strike glass components with hard or pointed items. DO NOT place very hot or very cold items against or in close proximity to glass surfaces unless an adequately thick insulation material is used to prevent such items coming in contact with the glass. The nominal thickness of the mirror glass used in this product is 1/4" and is film backed for safety. If the glass becomes chipped or broken replace immediately.


# INSTALLTION TOOLS NEEDED




# INSTALLTION MANUAL




**STEP 01:** Check the wall. Make sure that the wall is bearing walls that can support the Mirror's weight. Measure the width and height of the mirror back holes/hocks distance with a tape measure.




**STEP 02:** Mark the punching position on the wall with a pencil. Use level gauge make sure the hole at the same level.



**STEP 03:** Use impact drill punch holes in the marked center (6-8MM drill bit), the drilling depth is about 5CM. Use a hammer to drive the expansion screw into the drilled hole.



**STEP 04:** Use screwdriver screw the screw into the expansion screw, tighten. And then leave a distance of about 5MM from the wall.



**STEP 05:** Hand the mirror up with screw.